



Cat® 3516 Industrial Diesel Fire Pump Engines, with ratings: 1417-1480 kW (1900-1985 hp) @ 1460-1750 rpm, are non-certified, not FM Approved and not UL Listed. They are available for global non-regulated areas. Starting on demand is a must for a fire pump engine - always. Cat® fire pump engines have a reputation for reliable starts and long efficient service. The Cat line of fire engine pumps covers a wide range of installations.

## Specifications

Power Rating		
Maximum Power	1480 kW	1985 HP
Rated Speed	1460-1750 rpm	
Minimum Power	1417 kW	1900 HP

Emission Standards	
Emissions	Non-Certified. Available for global non-regulated areas. Not FM Approved. Not UL Listed

General		
Engine Configuration	V-16, 4-Stroke-Cycle Diesel	
Bore	170 mm	6.7 in
Stroke	190 mm	7.5 in
Displacement	69 l	4210 in <sup>3</sup>
Compression Ratio	13.0:1	
Aspiration	Turbocharged Aftercooled (TA)	
Rotation from Flywheel End	Counterclockwise	
Aftertreatment	-	

Engine Dimensions - Approximate		
Length	3730 mm	146.9 in
Height	1902 mm	74.9 in
Weight - Net Dry - Basic Operating Engine Without Optional Attachments	8074 kg	17800 lb

## Benefits and Features

**Reliable, Quiet and Durable Power**

World-class manufacturing capability and processes coupled with proven core engine designs assure reliability, quiet operation, and many hours of productive life.

#### **World-class Product Support Offered Through Global Cat Dealer Network**

- Scheduled maintenance, including SOSSM sample
- Customer Support Agreements (CSA)
- Caterpillar Extended Service Coverage (ESC)
- Superior dealer service network
- Extended dealer service network through the Cat Industrial Service Distributor (ISD) program

### **Standard Equipment**

#### **Air Inlet System**

- Air cleaner. Regular duty, dry, panel type with service indicators, turbocharger, jacket water aftercooled.
- Turbocharger, rear mounted
- Jacket water aftercooled

#### **Control System**

- Charging alternator 24 volt, 35 amp
- Governor, RH, 3161 with self contained synthetic oil sump
- Air-fuel ratio control
- Mechanical speed control, without torque control
- Governor control
- Positive locking

#### **Cooling System**

- Thermostats and housing
- Jacket water pump, centrifugal

#### **Exhaust System**

- Exhaust manifold, dry

#### **Flywheels and Flywheel Housing**

- SAE No. 0 flywheel
- 151 flywheel teeth
- SAE No. 0 flywheel housing
- SAE standard rotation

#### **Fuel System**

- Fuel filter, with service indicators, cartridge type with RH service
- Fuel transfer pump

#### **Instrumentation**

- Instrument Panel, RH
- Engine oil pressure gauge
- Fuel pressure gauge
- Oil filter differential gauge
- Jacket water temperature gauge

- Service meter, electric
- Tachometer

### **Lube System**

- Crankcase breather, top mounted
- Oil cooler
- Oil filler
- Oil dipstick
- Oil pump
- Oil filter, cartridge type with RH service
- Shallow oil pan
- Fumes disposal (not installed)

### **Mounting System**

- Rails, mounting, engine length, 254 mm (10 in), industrial-type, C-channel.
- Included on selected top level engines

### **Power Take Off**

- Accessory drive, upper RH
- Front housing, single sided

### **Protection System**

- Junction box
- Manual shutoff, RH
- Safety shutoff protection, energized to shutdown
- Low oil pressure, low idle 69 kPa (10 psi); high idle 207 kPa (30 psi)
- Water temperature
- Overspeed
- 3161 governor solenoid energized to shutdown

### **Starting System**

- Starting switch

### **General**

- Vibration damper
- Lifting eyes
- Paint: Caterpillar yellow, with optional colors available at request

The International System of Units (SI) is used in this publication. CAT, CATERPILLAR, their respective logos, ADEM, EUI, S•O•S, "Caterpillar Yellow" and the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.